

EA SPORTS™ NASCAR® Racing Track & Team Update Motion Platform Installation Instructions

Document Part #: 040-0199-MOT

Follow these instructions to install the Track & Team Update (Software Version 1.5) on your Motion Cabinet. Please keep these instructions in case you need to reinstall the software in the future.

Total Update takes about 25 minutes.

Important: Cabinets running this new software (Version 1.5) will not link to cabinets running previous versions.

Important: When you run the System Recovery Disk, you will erase all game settings, statistics, and collections data stored in the game software. Write down anything you want to remember before beginning the procedure.

Install the Game Dongle

1. Open the back of the Display Cabinet by removing the three interlocked panels. First remove the screws securing the top panel and remove that panel. Next remove the middle panel, and finally remove the lower panel.
2. Remove the USB Game Dongle from the system computer, and insert the new Game Dongle from the kit in the same USB Port.
3. **Please return the old dongle to GLOBAL VR for recycling:**

Mail dongles to: Dongle Returns, GLOBAL VR, 2350 Zanker Road, San Jose CA 95131

For your convenience, a pre-addressed envelope is included in the kit. (You can also use the envelope to return any other old dongles you may have.)

Put Monitor into PC Mode (if Needed)

If you don't see an image on your monitor once you start the software installation, you may need to put your monitor into PC mode.

Alternately, you can install the software without watching the progress on the monitor. Use the timing in this document to determine when each step is finished, and add a minute or so to each step as a precaution.

The steps to put your monitor into PC mode may vary depending on the specific monitor in use, so use the steps below as a guideline:

1. Press the **MENU** button on the TV Remote Control.
2. Use the scroll buttons (◀▶ ▲ ▼) to select **Input** from the onscreen menu, and then press ▶ repeatedly to select **HDMI-1**. (Make a note of the current setting to restore it later.)
3. Press ▲ ▼ repeatedly to change the setting for **HDMI-1** to **PC**, and then press **MENU** repeatedly to exit.

Run the System Recovery Disk

Note: Be careful not to scrape the CDs as you put them in the tray. Dirt or scratches on the surface of a CD can cause the software installation to fail.

1. Insert the **System Recovery Disk** in the drive and power the **computer OFF** and then **ON**.

Important: Do Not power cycle the cabinet. The monitor must remain **ON**. When the computer reboots, the CD should run automatically (wait about 30 seconds). You will see messages onscreen as files are copied to the hard drive.

2. After about 5 minutes, when prompted, remove the CD and reboot the computer. **Do not** insert the Game Install disk yet!
3. Wait for about 5—6 minutes while the software finishes the installation and reboots the computer. When the process is complete, you will briefly see a message saying "NASCAR OS Installation is Complete." The screen will say to Insert Game Disk 1, but for motion cabinets **you need to run the Motion Install Disk next**.

Run the Motion Install Disk

1. With the cabinet powered **ON** and the computer booted, insert the CD labeled **Motion Install**. The CD will automatically run (wait about 30 seconds).
2. The GLOBAL VR Motion Driver Install screen will appear as the software copies files from the disk, and then the computer will reboot and configure the software. The total process will take about 4 minutes, and then you will see a message saying "NASCAR OS Installation is Complete." Proceed to run the Game Install disk.

Run the Game Install Disk

1. With the cabinet powered **ON** and the computer booted, insert the CD labeled **Game Install**. The CD will automatically run (wait about 30 seconds). The Install Shield Wizard will appear as the software copies files to the hard drive.
2. After about 7—8 minutes, the computer will automatically reboot. A screen will appear saying "There is a CD in the Drive." Remove the CD and press the **START** button to continue. Keep the three CDs in a safe place in case you need them in the future.
3. The "Calibrate the Accelerator and Brake" screen will appear. Press each pedal fully to the floor to set the pot limits.
4. Next, the steering will auto calibrate. Do not touch the wheel as it turns to set the pot limits.
5. The Cabinet Link ID resets to **1** when you install the software. If the software detects another linked cabinet with that link ID number, a screen will appear and prompt you to select a different Link ID. If necessary, you can change link IDs from the Operator Menu.
6. If you changed the monitor to PC mode, follow the same steps to restore the pervious setting.
7. Once the Attract Movie begins, play a game to verify proper operation.
8. Open the Operator Menu and set the sound volume levels, pricing, and other Operator settings.

Install the *New Track & Road Course* Sign

Install the *New Track & Road Course* sign from the kit on top of the cabinet to let your players know about the update.